

mBIO-ST1

Access Control Terminal



INDUSTRIES SOLUTIONS



Education



Retail



Government



Healthcare



Hospitality



Bank



Office



Factory

mBio-ST1 can be used as a standalone access control reader by connecting a door lock, exit switch, alarm and door sensor to the relay contacts. The Wiegand IN and OUT ports can be used to connect 3rd party access control panels and peripherals. The mBio-ST1 also includes a USB port for offline data backup/management.



Fingerprint



RFID Card



USB Host



Access Control

Technical Specification

Color	Gray & Gold
Fingerprint capacity	1000
RFID card capacity	1000
Password records capacity	1000
Record capacity	100000 logs
Communication method	USB Drive
Access Controller	YES
Fingerprint scanner	High hardness optical fingerprint collection device
Authentication Method	Fingerprints, RFID card, Password and any combination
FRR	< 1%
FAR	< 0.0001%
Identification Time	< 0.5 Sec
Identification Mode	Fingerprint, RFID card, Pin
Wiegand input	WG 26/34
Power Adapter	DC 9V~12V
Excel Output	Yes

MANTRA SOFTECH (I) PVT. LTD.

E-mail: sales@mantratec.com,

Website : www.mantratec.com

CHANNEL PARTNER